ECO Range

Accessories Shower Outlet Flow Regulators

| | Specification | | | | | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|---------------------|-----------------------------------------|---------------------|---------------|-----------------------------------------------------------------------------------|
| | Product Code | Limited To (Ipm) | Minimum Dynamic Pressure (bar) | Connection Inlet | Fitted To | What's in the Box? |
| | ECO SHW 04 | 4 | 1 | G1/2" | Shower Outlet | 1x Screw- in Chrome housing with integral Grey 4lpm flow limiter |
| Features: Suitable for all bristan showers Between shower hose and handset All limiters accurate +/-10% Operating pressure range min 1.0 bar; max 5.0 bar Simply screw in place | ECO SHW 05 | 5 | 1 | G1/2" | Shower Outlet | 1x Screw- in Chrome housing with integral Yellow 5lpm flow limiter |
| | ECO SHW 06 | 6 | 1 | G1/2" | Shower Outlet | 1x Screw- in Chrome housing with integral Black 6lpm flow limiter |
| Product Certifications: EXERCISE WRAS Certificate No: 2007800 WRAS Expiry Date: 31/07/2025 | ECO SHW 07 | 7 | 1 | G1/2" | Shower Outlet | 1x Screw- in Chrome housing with integral Green 7lpm flow limiter |
| | ECO SHW 08 | 8 | 1 | G1/2" | Shower Outlet | 1x Screw- in Chrome housing with integral White 8lpm flow limiter |
| For more products, visit our website: http://www.bristan.com | ECO SHW 10 | 10 | 1 | G1/2" | Shower Outlet | 1x Screw- in Chrome housing with integral Blue 10lpm flow limiter |
| | ECO SHW 14 | 14 | 1 | G1/2" | Shower Outlet | 1x Screw- in Chrome housing with integral Pink 14lpm flow limiter |

TECHNICAL DATA SHEET



Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.